



Technical features

| Item Id. | EP-030663 |
|--------------------------------------|--|
| drive turning direction | R.H./L.H. |
| drive speed max | permanent operation 645 - 10.968 rpm |
| drive speed max | interval operation 645 - 12.903 rpm |
| number of spindles | 1 |
| spindle position | horizontal |
| tool receptacle | 1x milling receptacle ø30h7 x 40 mm |
| turning direction of tool receptacle | 1x equal to drive turning direction |
| gear ratio | 1 : 1,55 – wheel drive |
| spindle speed | permanent operation 1.000 – 17.000 rpm |
| spindle speed | interval operation 1.000 – 20.000 rpm |
| max. spindle capacity | 3,0 kW |
| weight with drive adapter | approx. 4,00 kg |

Optional accessories:

| | |
|-----------------------------|-----------------|
| Open end spanner SW 41 flat | Item Id. 131203 |
| Hook wrench 40/42 | Item Id. 139040 |
| Lubrication press | Item Id. 980003 |

The angular heads of the series G06-1.1-F have a continuous machining spindle. The drive speed is transmitted in a ratio 1:1,55 to the tool receptacles. The maximum spindle speed in interval operation is 20,000 rpm.

Note:

We point out that tools must be authorized for their choice of speeds!

Variants on demand!

