



Technical features

Item Id.	EP-030648
drive turning direction	R.H./L.H.
drive speed max.	permanent operation 645 – 9.290 rpm
drive speed max.	interval operation 645 – 11.613 rpm
number of spindles	4
spindle position	horizontal
tool receptacle	3x $\varnothing 10\text{ H7}$ with binding screw
tool receptacle	1x Hi-Q/ERM25 DIN6499-C (8°)
gear ratio	1 : 1,55 – wheel drive
turning direction of tool receptacle	4x equal to drive turning direction
spindle speed max.	permanent operation 1.000 - 14.400 rpm
spindle speed max.	interval operation 1.000 - 18.000 rpm
drive capacity	3,0 kW
weight with drive adapter	approx. 5,30kg

Optional accessories:

Hex-wrench SW3	Item Id. 138030
Open end spanner SW17	Item Id. 131017
Open end spanner SW36 flat	Item Id. 131236
Hook wrench E25M	Item Id. 137002
Lubrication press	Item Id. 980003

The angular heads of the series G03 are equipped with up to 4 processing spindles. The spindle turning direction of all tool receptacles is always equal to the drive turning direction. The drive speed is transmitted in a ratio of 1:1,55 to the tool receptacles. The maximum spindle speed in interval operation is 18,000 rpm.

Variants on demand!

